

US009118387B2

(12) United States Patent

Padovani et al.

(10) Patent No.: US 9,118,387 B2

(45) **Date of Patent:** *Aug. 25, 2015

(54) PILOT REFERENCE TRANSMISSION FOR A WIRELESS COMMUNICATION SYSTEM

(75) Inventors: Roberto Padovani, San Diego, CA

(US); Peter J. Black, San Diego, CA

(US); Nagabhushana T.

Sindhushayana, San Diego, CA (US)

(73) Assignee: QUALCOMM Incorporated, San

Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 1285 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 11/858,840

(22) Filed: **Sep. 20, 2007**

(65) **Prior Publication Data**

US 2008/0008136 A1 Jan. 10, 2008

Related U.S. Application Data

(63) Continuation of application No. 09/702,142, filed on Oct. 30, 2000, now Pat. No. 7,289,473, and a continuation-in-part of application No. 09/575,073, filed on May 19, 2000, now Pat. No. 6,894,994, and a

(Continued)

(51) **Int. Cl. H04L 12/28 H04B 7/26**

(2006.01) (2006.01)

(Continued)

(52) **U.S. Cl.**

(58) Field of Classification Search

CPC .. H04W 72/0446; H04W 84/12; H04W 84/18

(56) References Cited

U.S. PATENT DOCUMENTS

3,018,663 A 1/1962 Dunlop 3,534,264 A 10/1970 Blasbalg et al.

(Continued)

FOREIGN PATENT DOCUMENTS

BR 9607900 A 1/1998 BR 9607621 A 6/1998 (Continued) OTHER PUBLICATIONS

3RD Generation Parternership project, Technical specification group radio access network 25.101 section 9.3, User equipment (UE) Radio Transmission and Reception (FDD, Release Jun. 12, 2005.

(Continued)

Primary Examiner — John Pezzlo (74) Attorney, Agent, or Firm — Dalei Dong

(57) ABSTRACT

A pilot reference transmission scheme well suited for high data rate wireless communication systems is disclosed. To maximize the amount of interference from transmissions from neighboring transmission sources (e.g., access points or base stations) during the pilot interval, and hence minimize the amount of interference from non-transmitting sources during the data intervals, the pilot references are transmitted in bursts at predetermined time intervals, and the pilot bursts from the access points are synchronized. This results in maximum interference contributions from non-transmitting neighboring access points, facilitating reliable estimation of worst case carrier-to-interference (C/I), and further allows the receiving devices (e.g., access terminals) to easily recognize the bursts as pilot reference. In one embodiment, each access point transmits the pilot bursts at or near its maximum transmit power level and no user-specific data is transmitted during the pilot bursts.

21 Claims, 7 Drawing Sheets



